



MP1100E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating at	- 50Hz	
400V	KVA		KW
Prime	1000.0		800.0
Standby	1100.0		880.0
			@ 0.8 p.f.
Generator Outp	out Rating at	: - 60Hz	
480V	KVA		KW
Prime	N/A		N/A
Standby	N/A		N/A
			@ 0.8 p.f.
Engine Data			
Engine Manufact	urer:	Perkins L	JK
Engine Manufact Engine Model:		Perkins U 4008-30TA	
	ı		
Engine Model:	lers:	1008-30TA	AG2
Engine Model: Number of Cylind	lers:	4008-30TA 8	AG2 Line
Engine Model: Number of Cylind Cylinder Arranger	lers: ment: V	4008-30TA 8 'ertical In	AG2 Line
Engine Model: Number of Cylind Cylinder Arranger Cycle:	lers: ment: V (in): 160.0	4008-30TA 8 /ertical In 4 Stroke	AG2 Line 2 0.0 (7.5) air-to-air
Engine Model: Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	lers: ment: V (in): 160.0 Turbo	4008-30TA 8 'ertical In 4 Stroke (6.3) / 19 charged &	AG2 Line 2 0.0 (7.5) air-to-air

Liter	US/Gal	
N/A	N/A	
N/A		
Heavy Duty-Powder Coated		
Deep Sea Electronics		
ABB 3 Pole MCCB		
	N/ Heavy Duty-Po Deep Sea E	

Performance	50	Hz	60	HZ
Engine Speed:	15	00	18	800
Gross Engine Power:	kWm	Bhp	kWm	Bhp
Prime:	901	1208.0	N/A	N/A
Standby:	997	1256.0	N/A	N/A
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	211	55.7	N/A	N/A
Standby:	234	62.0	N/A	N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Centimeter Inch Centimeter Inch KG LB KG LI		
	KG LB	
450.4 177.0 219.4 86.4 205.0 80.7 7236.0 15953.0 8000.0 176	8000.0 17637.0	

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	Hz	60	Hz
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	84	2966	N/A	N/A
Exhaust Gas Flow:	203	7168	N/A	N/A
Radiator Cooling: Air Flow	1104	38987	N/A	N/A

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer: Leroy Somer

Alternator Model: LSA49.3 L10 | TAL049E

Number of Bearings: Single (1)

Insulation Class: H

Total Harmonic Content: < 4% | < 5%

Wires: 6

Ingress Protection Rating: IP 23

Excitation System: AREP | Shunt



Winding Pitch Code:

Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.

2/3 - 6S



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50	Hz	60)Hz
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	140.0	37.0	N/A	N/A
Lube Oil Capacity:	153.0	40.4	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	473	883	N/A	N/A

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:

JAN2014 VER.1