



MP110E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 50Hz				
400V	KVA			KW
Prime	10	0.0		80.0
Standby	11	0.0		88.0
				@ 0.8 p.f.
Generator Outp	out Rat	ing at -	60H	Z
480V	K	VA		KW
Prime	11	4.4		91.5
Standby	12	6.5		101.2
				@ 0.8 p.f.
Engine Data				
Engine Manufacturer: Perkins UK				
_	aici.	F	етки	IS UK
Engine Model:	uici.			4TAG2
Engine Model: Number of Cylind				44TAG2
•	lers:	110	04C-4 4	44TAG2
Number of Cylind	lers:	110	04C-4 4	I4TAG2 In Line
Number of Cylind	lers: ment:	110 Ver	04C-4 4 rtical 4 Str	I4TAG2 In Line
Number of Cylind Cylinder Arrange Cycle:	lers: ment: (in):	110 Vei 105.0 (4 Turboch	04C-4 4 rtical 4 Str 4.1) x arged	I4TAG2 In Line oke
Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	lers: ment: (in):	110 Vei 105.0 (4 Turboch	04C-4 4 rtical 4 Str 4.1) x arged	I4TAG2 In Line oke 127.0 (5.0) d & air-to-air cooled

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	220.0	58.1		
Fuel Tank:	UV Resistant MDPE			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

Performance	50Hz		60	60HZ	
Engine Speed:	1500		1800		
Gross Engine Power:	kWm	Bhp	kWm	Bhp	
Prime:	93.6	125.5	106.8	143.1	
Standby:	103.0	138.1	117.5	157.6	
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr	
Prime:	22.6	5.97	26.9	7.106	
Standby:	24.9	6.578	29.7	7.846	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Leng	gth	Wic	lth	Hei	ght	I	Dry	,	Wet
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB
217.0	85.4	77.0	30.4	146.0	57.5	1169.0	2577.0	1189.0	2621.0

* With Lube Oil & Coolant

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	50Hz		Hz
	M³∕min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	6.27	221	7.8	275
Exhaust Gas Flow:	16.3	576	20.4	720
Radiator Cooling: Air Flow	165.6	5848	225.6	7967

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacture	r: Leroy Somer
Alternator Model:	LSA44.3 S5 TALO44D
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 5%
Wires:	12 <i>6</i>
Ingress Protection Rating	: IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	12.6	3.3	12.6	3.3
Lube Oil Capacity:	8.0	2.1	8.0	2.1
	°C	°F	°C	°F
Exhaust Temperature:	543	1009	574	1065



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



0407/2017