

# **MP14E**

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	out Rating a	t - 50Hz		
400V	KVA		KW	
Prime	12.5		10.0	
Standby	14.0		11.2	
			@ 0.8 p.f.	
Generator Out	out Rating a	t - 60Hz		
380V	KVA		KW	
Prime	N/A		N/A	
Standby	N/A		N/A	
			@ 0.8 p.f.	
Engine Data				
Engine Data Engine Manufact	urer:	Perkins UK		
-	urer:	Perkins UK 403A-15G		
Engine Manufact				
Engine Manufact Engine Model:	ders:	403A-15G		
Engine Manufact Engine Model: Number of Cyling	ders:	403A-15G 3		
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange	ders: ment:	403A-15G 3 Vertical In Lii	ne	
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle:	ders: ment: (in): 84.4	403A-15G 3 Vertical In Lii 4 Stroke	ne (3.5)	
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	ders: ment: ' (in): 84.4	403A-15G 3 Vertical In Lin 4 Stroke 4 (3.3) x 90.0	ne (3.5)	

General Data					
	Liter	US/Gal			
Fuel Tank Capacity:	100.0	26.4			
Fuel Tank:	UV Resistant MDPE				
Base Frame:	Heavy Duty-Po	owder Coated			
Control Panel:	Deep Sea Electronics				
Circuit Breaker:	ABB 3 Po	ole MCB			

Performance	50	Hz	60HZ		
Engine Speed:	15	1500		1800	
<b>Gross Engine Power:</b>	kWm Bhp		kWm	Bhp	
Prime:	12.2	16.4	N/A	N/A	
Standby:	13.5	18.1	N/A	N/A	
<b>Fuel Consumption:</b>	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr	
Prime:	3.67	0.97	N/A	N/A	
Standby:	4.08	1.08	N/A	N/A	
			,		

#### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

## **Dimensions and Weights**

Len	gth	Wid	lth	Hei	ght	I	Dry	,	Wet
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB
132.5	52.2	72.0	28.3	119.0	46.8	340.0	750	352.0	776.0
						* With Lube Oil		* With Lube Oil	& Coolant

## **Rating Definition**



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	1.10	39	N/A	N/A
Exhaust Gas Flow:	2.9	102	N/A	N/A
Radiator Cooling: Air Flow	36.6	1292	N/A	N/A

<sup>\*</sup>Cooling system designed to operate in high ambient conditions

#### **Alternator Data**

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA40 VS2   TAL040C
Number of Bearings:	Single (1)
Insulation Class:	Н
<b>Total Harmonic Content:</b>	<b>&lt; 5</b> %   <i>&lt; 5</i> %
Wires:	<b>12</b>   <i>6</i>
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$ 

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	6.0	1.59	N/A	N/A
Lube Oil Capacity:	6.0	1.59	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	490	914	N/A	N/A

## **Other Information**

### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

#### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

# Distributed & Serviced by:



JAN2014 VER.1