



# MP2000E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating at	- 50Hz					
400V	KVA		KW				
Prime	1850.0		1480.0				
Standby	2000.0		1600.0				
	2000.0		@ 0.8 p.f.				
Generator Output Rating at - 60Hz							
480V	KVA		KW				
Prime	N/A		N/A				
Standby	N/A		N/A				
-			@ 0.8 p.f.				
Engine Data							
Engine Manufa	acturer:	Perkins UK					
Engine Model:		4016-61TRG1					
•		4016-6	1TRG1				
Number of Cyl			6				
Number of Cyl Cylinder Arran	inders:	1	-				
•	inders:	1 60"	6				
Cylinder Arran	inders: gement:	1 60*` 4 Str	6 Vee roke				
Cylinder Arran Cycle:	inders: gement:	1 60 4 Str 160.0 (6.3) / Turboo	6 Vee roke / 190.0 (7.5) charged				
Cylinder Arran Cycle: Bore/Stroke m	inders: gement: nm (in):	1 60 4 Str 160.0 (6.3) / Turboo	6 Vee roke / 190.0 (7.5) charged charge cooled				

# **General Data**

	Liter		US/G	Gal		
Fuel Tank Capacity:	N/A		N//	Д		
Fuel Tank:	ank: N/A					
Base Frame:	Base Frame: Heavy Duty-Powder Coated					
Control Panel: Deep Sea Electronics						
Circuit Breaker: ABB 3 Pole ACB						
*Breaker supplied loose in a standalone cabinet on open type generating sets						
Performance 50Hz 60Hz						
Engine Speed:	150	1500		1800		
Gross Engine Power	kWm	Bhp	kWm	Bhp		
Prime:	1648	2210	N/A	N/A		
Standby:	1774	2379	N/A	N/A		
	1774	2379	N/A	N/A		
Standby: Fuel Consumption:		2379 US Gal/Hr	N/A L/Hr	N/A US Gal/Hr		
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr		

#### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Leng	gth	Widt	h	Heig	ht	Dr	Ņ	W	et
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB
562.3	221.4	222.5	87.6	346.1	136.3	13200	29321	13500	29762
			* With Lube Oil		* With Lube Oil	& Coolant			

# **Rating Definition**

# P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

# S Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50 H	lz	60 Hz		
	M∛min <i>F</i>	t'/min	M∛min	Ft <sup>³</sup> /min	
Combustion Air Flow:	165 5	5827	N/A	N/A	
Exhaust Gas Flow:	400 1	4125	N/A	N/A	
Radiator Cooling Air Flow:	2160 7	6279	N/A	N/A	

\*Cooling system designed to operate in high ambient conditions

#### **Alternator Data**

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA52.3 S5
Number of Bearings:	Single (1)
Insulation Class:	н
Total Harmonic Content:	< 5%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP + PMI
Winding Pitch Code:	2/3 - (n°6S)

# Principles

**B** Perkins<sup>®</sup> Diesel Power

Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are Registered Trademarks

<b>Cooling &amp; Lubrication</b>	5	0 Hz	60	60 Hz		
	Liter	US/Gal	Liter	US/Gal		
Coolant Capacity:	385	55.5	N/A	N/A		
Lube Oil Capacity:	213	56.3	N/A	N/A		
	c	'F	"C	"F		
Exhaust Temperature:	425	797	N/A	N/A		



## **Other Information**

#### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

## Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

# Distributed & Serviced by:

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com