



MP200E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output	Rating at -	50H	lz	
400V	KVA		KW	
Prime	180.0		144.0	
Standby	200.0		160.0	
			@ 0.8 p.f.	
Generator Output	Rating at -	60H	lz	
480V	KVA		KW	
Prime	N/A		N/A	
Standby	N/A		N/A	
			@ 0.8 p.f.	
Engine Data				
Engine Data Engine Manufacture	r: Pe	rkins	s UK	
_			UK DTAG3	
Engine Manufacture	1106			
Engine Manufacture Engine Model:	1106	6 6		
Engine Manufacture Engine Model: Number of Cylinders	1106 : nt: Vert	6 6	n Line	
Engine Manufacture Engine Model: Number of Cylinders Cylinder Arrangemer	1106 : nt: Vert	6 6 ical I	n Line	
Engine Manufacture Engine Model: Number of Cylinders Cylinder Arrangemer Cycle:	1106 : nt: Vert 4 : 105.0 (4. Turbo cha	6 ical II Stro 1) / 2	n Line ke	
Engine Manufacture Engine Model: Number of Cylinders Cylinder Arrangemer Cycle: Bore/Stroke mm (in)	1106 : nt: Vert 4 : 105.0 (4. Turbo cha	6 ical II Stro 1) / 2	n Line ke 135.0 (5.3) & air-to-air	

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	400.0	116.2		
Fuel Tank:	Powder Coated Steel			
Base Frame:	Heavy Duty-Po	owder Coated		
Control Panel:	Deep Sea E	Electronics		
Circuit Breaker:	ABB 3 Pole MCB			

50Hz		60HZ	
150	00	1800	
kWm	Bhp	kWm	Bhp
168.6	226.1	N/A	N/A
185.5	248.7	N/A	N/A
L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
41.4	10.9	N/A	N/A
45.1	11.9	N/A	N/A
	150 kWm 168.6 185.5 L/Hr 41.4	1500 kWm Bhp 168.6 226.1 185.5 248.7 L/Hr US Gal/Hr 41.4 10.9	1500 18 kWm Bhp kWm 168.6 226.1 N/A 185.5 248.7 N/A L/Hr Us Gal/Hr L/Hr 41.4 10.9 N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wid	dth	He	ight	[Dry	1	Net
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB
269.2	106.0	100.0	39.4	167.0	65.8	1726.0	3805.0	1760.0	3880.0

* With Lube Oil & Coolant

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz		
	M³/min Ft³/min	M³/min Ft³/min		
Combustion Air Flow:	13.87 489.8	N/A N/A		
Exhaust Gas Flow:	33.85 1195.0	N/A N/A		
Radiator Cooling: Air Flow	164.0 5791	N/A N/A		

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA44.3 VL13 TAL044L
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	<5% < 5%
Wires:	12 <i>6</i>
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	20.5	5.41	N/A	N/A
Lube Oil Capacity:	18.0	4.75	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	491	915	N/A	N/A



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



7-2015 REV.1