



MP330E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	out Rating at	- 50Hz					
400V	KVA	KW					
Prime	300.0	240.0					
Standby	330.0	264.0					
		@ 0.8 p.f.					
Generator Output Rating at - 60Hz							
480V	KVA	KW					
Prime	338.0	270.4					
Standby	375.0	300.0					
		@ 0.8 p.f.					
Engine Data							
Engine Data Engine Manufact	urer: Pe	rkins USA					
<u> </u>		rkins USA 5A-E88TAG5					
Engine Manufact	1506						
Engine Manufact Engine Model:	1506 lers:	5A-E88TAG5					
Engine Manufact Engine Model: Number of Cyline	1506 lers: ment: Ver	5A-E88TAG5 6					
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange	1506 lers: ment: Ver	5A-E88TAG5 6 tical In Line					
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle:	1506 ders: ment: Ver (in): 112 (4 Turbo cha	5A-E88TAG5 6 tical In Line 4 Stroke					
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	1506 ders: ment: Ver (in): 112 (4 Turbo cha Cha	5A-E88TAG5 6 tical In Line 4 Stroke .4) / 149 (5.9) arged & air-to-air					

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	600	158.5		
Fuel Tank:	Powder Coated Steel			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCCB			

Performance	50Hz		60HZ	
Engine Speed:	150	1500		00
Gross Engine Power:	kWm	kWm Bhp		Bhp
Prime:	281.0	376.7	325.0	435.6
Standby:	307.0	307.0 411.5		479.8
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	64.9	17.1	77.1	20.4
Standby:	73.1	19.3	85.7	22.6

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Len	gth	Wic	lth	Hei	ght		Dry		Wet
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB
381.4	150.0	110.6	43.5	178.0	70.0	2820.0	6217.0	2860.0	6305.0
						* With Lube Oi		* With Lube Oil	& Coolant

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF

Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

Rating Definition

P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³∕min	Ft³∕min	M∛min	Ft∛min
Combustion Air Flow:	18.3	646.2	23.6	833.4
Exhaust Gas Flow:	50.0	1765.7	59.6	2104.7
Radiator Cooling: Air Flow	370	13066	482	17022

*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 46.3 M8 TAL046F
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	<5% <i><</i> 5%
Wires:	12 <i>6</i>
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 (n° 6)



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

50Hz		6()Hz
Liter	US/Gal	Liter	US/Gal
33.2	8.7	33.2	8.7
41.0	10.8	41.0	10.8
°C	°F	°C	°F
574	1065.2	512	953.6
	Liter 33.2 41.0 °C	Liter US/Gal 33.2 8.7 41.0 10.8 °C °F	Liter US/Gal Liter 33.2 8.7 33.2 41.0 10.8 41.0 °C °F °C



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com