



MP400E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Ra	ating at -	50Hz		
400V	KVA		KW	
Prime 3	350.0		280.0	
Standby 4	0.004		320.0	
			@ 0.8 p.f.	
Generator Output R	ating at -	60Hz		
480V	KVA		KW	
Prime 2	100.0		320.0	
Standby	438.0		350.0	
			@ 0.8 p.f.	
Engine Data				
Engine Manufacturer:	Po	erkins U	SA	
Engine Model:	220	6A-E137	TAG2	
Number of Cylinders:		6		
Cylinder Arrangement:	Vei	rtical In	Line	
Cycle:		4 Stroke	è	
Bore/Stroke mm (in):	130.0 (5	5.1) / 15	7.0 (6.1)	
Induction:		arged & arge cod	air-to-air oled	
Compression ratio	16.3:1			
Compression ratio:		10.5.1		

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	940.0	248.4		
Fuel Tank:	Powder Coated Steel			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCCB			

Performance	50Hz		60	60HZ	
Engine Speed:	1500		18	00	
Gross Engine Power:	kWm	Bhp	kWm	Bhp	
Prime:	324.2	434.8	373.4	500.7	
Standby:	368.4	494.0	406.5	545.1	
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr	
Prime:	71	18.76	81	21.4	
Standby:	80	21.13	87	22.98	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wid	lth	Hei	ght	[Dry	,	Wet
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB
381.3	150.0	112.0	44.1	213.8	84.2	3663.0	8075.0	3723.0	8207.0

* With Lube Oil

* With Lube Oil & Coolant

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	50Hz		Hz
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	26.4	932	29.0	1024
Exhaust Gas Flow:	72.5	2560	73.5	2596
Radiator Cooling: Air Flow	563.0	19882	716.0	25285

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA46.3 L11 TAL046H
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 5 % <i><</i> 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	51.4	13.6	51.4	13.6
Lube Oil Capacity:	40.0	10.6	40.0	10.6
	°C	°F	°C	°F
Exhaust Temperature:	630	1166	660	1220



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:

JAN2014 VER.1