



# **MP66E**

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating a	at - 50Hz	
400V	KVA		KW
Prime	60.0		48.0
Standby	66.0		52.8
			@ 0.8 p.f.
Generator Outp	out Rating a	at - 60Hz	
480V	KVA		KW
Prime	68.1		54.5
Standby	75.1		60.1
			@ 0.8 p.f.
Engine Data			-
Engine Data Engine Manufact	urer:	Perkins	UK
<u> </u>	urer:	Perkins 1103A-33	•
Engine Manufact			•
Engine Manufact Engine Model:	lers:	1103A-33	TG2
Engine Manufact Engine Model: Number of Cyline	lers:	1103A-33 3	TG2 Line
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange	lers: ment:	1103A-33 3 Vertical In	TG2 Line
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle:	lers: ment:	1103A-33 3 Vertical In 4 Strok	TG2 Line e 27.0 (5.0)
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	<b>lers:</b> ment: <i>(in):</i> 105.	1103A-33 3 Vertical In 4 Strok 0 (4.1) x 12	TG2 Line e 27.0 (5.0) rged

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	220.0	58.1		
Fuel Tank:	UV Resistant MDPE			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

Performance	50H	50Hz		HZ
Engine Speed:	150	1500		00
Gross Engine Power:	kWm	kWm Bhp		Bhp
Prime:	55.0	73.8	63.3	84.9
Standby:	60.5	81.1	69.6	93.3
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	14.6	3.857	16.6	4.385
Standby:	15.9	4.200	18.2	4.808

### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Len	gth	Wie	dth	Hei	ight	[	Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2200.0	86.6	760.0	29.9	1465.0	57.7	799.0	1761.5	820.0	1807.8
* With Lube Oil * With Lube Oil & Coolant							l & Coolant		

### **Rating Definition**

### P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

## Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	Hz	60Hz		
	M³∕min	Ft³∕min	M∛min	Ft∛min	
Combustion Air Flow:	3.9	138	4.9	173	
Exhaust Gas Flow:	10.4	367	12.5	441	
Radiator Cooling: Air Flow	89.0	3134	111.0	3920	

\*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA42.3 L9   TAL042H
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	<b>&lt; 4%</b>   <i>&lt;</i> 5%
Wires:	12   6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

			60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	10.2	2.7	10.2	2.7
Lube Oil Capacity:	8.3	2.2	8.3	2.2
	°C	°F	°C	°F
Exhaust Temperature:	571	1060	564	1047
Lube Oil Capacity:	8.3 °C	2.2 °F	8.3 °C	3



#### **Other Information**

### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

### Distributed & Serviced by:



Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com