

# **MP800E**

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating at	: - 50Hz
400V	KVA	KW
Prime	725.0	580.0
Standby	800.0	640.0
		@ 0.8 p.f
Generator Outp	out Rating at	: - 60Hz
480V	KVA	KW
Prime	725.0	580.0
Standby	800.0	640.0
		@ 0.8 p.f
Engine Data		
Engine Manufact	urer:	Perkins UK
Engine Manufact Engine Model:		Perkins UK 006-23TAG2A
-	4	
Engine Model:	4 lers:	006-23TAG2A
Engine Model: Number of Cylinc	4 lers:	006-23TAG2A 6
Engine Model: Number of Cylinc Cylinder Arrange	4 lers: ment: V	006-23TAG2A 6 /ertical In Line
Engine Model: Number of Cylinc Cylinder Arranger Cycle:	4 lers: ment: V (in): 160.0 Turbo (	006-23TAG2A 6 /ertical In Line 4 Stroke
Engine Model: Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	4 Iers: ment: V ( <i>in</i> ): 160.0 Turbo ( C	006-23TAG2A 6 /ertical In Line 4 Stroke (6.3) / 190.0 (7.5) charged & air-to-air

## General Data

	Liter	US/Gal			
Fuel Tank Capacity:	N/A	N/A			
Fuel Tank:	N/A				
Base Frame:	Heavy Duty-Powder Coated				
Control Panel:	Deep Sea Electronics				
Circuit Breaker:	ABB 3 Pole MCCB				

Performance	50	Hz	60HZ	
Engine Speed:	150	1500		800
Gross Engine Power:	kWm	Bhp	kWm	Bhp
Prime:	658.0	882.0	682.0	914.6
Standby:	721.0	967.0	746.0	1000.0
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	172.0	45.4	199.0	52.5
Standby:	193.0	50.9	224.0	59.2

### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

\* With Lube Oil & Coolant

Please consult your dealer for specific site ratings.

\* With Lube Oil

# Dimensions and Weights

Len	gth	Wid	th	Hei	ght	[	Dry	,	Wet	
Centimeter	Inch	Centimeter	Inch	Centimeter	Inch	KG	LB	KG	LB	
438.2	172.5	193.3	76.1	223.3	87.9	5862.0	12923.0	6000.0	13228.0	

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

### **Rating Definition**

# P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

# Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³∕min	Ft³∕min	M³∕min	Ft³∕min
Combustion Air Flow:	71.0	2507	72.0	2543
Exhaust Gas Flow:	180.0	6357	190.0	6710
Radiator Cooling: Air Flow	870.0	30724	1140.0	40258

\*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 49.3 M6   TAL049B
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	<b>&lt; 5%</b>   <i>&lt;</i> 5%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP   Shunt
Winding Pitch Code:	2/3 - 65



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

<b>Cooling &amp; Lubrication</b>	5(	)Hz	6(	)Hz	
	Liter	US/Gal	Liter	US/Gal	
Coolant Capacity:	120	31.7	120.0	31.7	
Lube Oil Capacity:	113.0	30.0	113.0	30.0	
	°C	°F	°C	°F	
Exhaust Temperature:	500	932	500	932	



#### **Other Information**

### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

### Distributed & Serviced by:



Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com