



MP66E Canopy

- Marapco sound attenuated, weatherproof enclosures are manufactured from heavy gauge galvanised sheet steel (polyester powder painted for rust-proofed protection).
- Enclosures are fitted with extra-thick, high-density acoustic grade foam for superior performance. Access is provided by wide aperture lockable doors with corrosion resistant fasteners.
- The residential silencer is mounted internally for enhanced performance and heavy-duty lifting eyes are provided on the baseframe as standard.

Canopy Features, Benefits & Extras


Standard Options


- Polyester powder coated galvanised steel
- Fuel tank and filler cap
- Rain cap and vertical air outlet
- Fuel/water separator
- Exhaust Silencer & manifold stud pipe
- Emergency Stop push button
- Heavy duty doors, hinges and latches
- Controller display window

Optional Extras

- Certified single lift point
- Retaining door bars
- Integrated spark arrestor
- Fire shut off valves
- Automatic fuel top-up
- Manual oil pump
- AC 3ph/1ph output sockets

Canopy Data





Standard reference conditions: 25deg C (77deg F) air inlet temperature, 152.4m (500feet) above sea level, 60% relative humidity.

Dimensions: mm	
Length (A)	2385
Width (B)	1100
Height (C)	1819
Max projection (D)	763
Max. Width (E)	1098
Max Height (F)	N/A

Weights: kg	
Dry Weight (with lube oil)	1383
Wet Weight (lube oil and coolant)	1397

Sound Pressure Levels: dB(A)			
	50Hz	60Hz	
15m, 75% load	57.9	TBA	
15m, 100% load	60	TBA	
7m, 75% load	62.2	TBA	
7m, 100% load	63.4	TBA	
1m, 75% load	71	TBA	
1m, 100% load	72.5	TBA	

*In line with our policy of continuous development, we reserve the right to change specification without notice. Specification and canopy data should